



CONSTRUCTION: Lead-Free Brass
MOUNT TYPE: Deck Mounted
CARTRIDGE: Ceramic Cartridge
INLET CONNECTIONS: ½" BSP
WORKING PRESSURES: 0.50 – 10.0 Bar
OPERATING TEMPERATURE: 5°C – 80°C
SUPPLY: Suitable for all plumbing Systems
OPERATION: Single lever flow & temperature control

- Made from brass to preserve water quality
- Sedal ceramic cartridges for smooth operation
 - Neoperl constant flow aerator
 - Tucai hot and cold water inlet hoses
 - Available in assorted finishes

OPEN OUTLET FLOW (Bar – l/min)

15 Year Guarantee

Bar	0.3	0.5	1.0	2.0	3.0	4.0	5.0
Spout Flow	2.95	4.2	4.6	4.35	4.5	4.6	4.4

Please Note: Flow rate will be dictated by installation configurations. Please ensure to check the appropriate flow restrictor information if applicable. Please refer to the website for fully warranty details.

CERTIFICATION:

- WRAS APPROVED: 1811350
- UPC
- CE
- WATERPARK

FURTHER DETAILS & DIMENSIONS CAN BE FOUND AT WWW.LUSSOSTONE.COM IN THE FEATURE SECTION AND DOWNLOADS TAB OF EACH PRODUCT PAGE.