



CONSTRUCTION: Lead-Free Brass

MOUNT TYPE: Deck Mounted

CARTRIDGE: Ceramic Cartridge

INLET CONNECTIONS: ½" BSP

WORKING PRESSURES: 0.50 – 10.0 Bar

OPERATING TEMPERATURE: 5°C – 80°C

SUPPLY: Suitable for all plumbing Systems

OPERATION: Single lever flow & temperature control

Made from brass to preserve water quality

- Sedal ceramic cartridges for smooth operation
- Neoperl constant flow aerator
- Tucai hot and cold water inlet hoses
- Available in assorted finishes

OPEN OUTLET FLOW (Bar – l/min)

15 Year Guarantee

Bar	0.3	0.5	1.0	2.0	3.0	4.0	5.0
Spout Flow	2.95	4.2	4.6	4.35	4.5	4.6	4.4

Please Note: Flow rate will be dictated by installation configurations. Please ensure to check the appropriate flow restrictor information if applicable. Please refer to the website for fully warranty details.

CERTIFICATION:

- WRAS APPROVED
- UPC
- CE
- WATERPARK

FURTHER DETAILS & DIMENSIONS CAN BE FOUND AT WWW.LUSSOSTONE.COM IN THE FEATURE SECTION AND DOWNLOADS TAB OF EACH PRODUCT PAGE.

TEL: 0203 370 40571

EMAIL: INFO@LUSSOSTONE.COM

| WWW.LUSSOSTONE.COM

THE INFORMATION ON THIS SPECIFICATION DOCUMENT WAS CORRECT AT THE DATE OF ISSUE. SOME VARIATION MAY OCCUR DUE TO MANUFACTURING TOLERANCES AND SITE-SPECIFIC CONDITIONS.