



CONSTRUCTION: Lead-Free Brass

MOUNT TYPE: Wall Mounted

CARTRIDGE: Ceramic Cartridge

INLET & OUTLET CONNECTIONS: ½" BSP

WORKING PRESSURES: 0.50 – 10.0 Bar

OPERATING TEMPERATURE: 5°C – 80°C

SUPPLY: Suitable for all plumbing Systems

OPERATION: Single lever flow & temperature control

- Made from brass to preserve water quality
- Citec ceramic cartridges for smooth operation
- Neoperl constant flow aerator
- Available in assorted finishes
- Solid brass lever

OPEN OUTLET FLOW (Bar – l/min)

15 Year Guarantee

Bar	0.5	1.0	1.5	2.0	3.0	4.0	5.0
Spout Flow	3.1	4.3	4.8	4.9	4.6	4.8	4.5

Please Note: Flow rate will be dictated by installation configurations. Please ensure to check the appropriate flow restrictor information if applicable. Please refer to the website for fully warranty details.

CERTIFICATION:

- WRAS APPROVED:
- UPC
- CE
- WATERPARK

FURTHER DETAILS & DIMENSIONS CAN BE FOUND AT WWW.LUSSOSTONE.COM IN THE FEATURE SECTION AND DOWNLOADS TAB OF EACH PRODUCT PAGE.