



**CONSTRUCTION:** Lead-Free Brass

**MOUNT TYPE:** Wall Mounted

**CARTRIDGE:** Thermostatic Cartridge

**SHOWER VALVE INLET CONNECTIONS:** G 3/4"

**SHOWER VALVE OUTLET CONNECTIONS:** G 1/2"

**WORKING PRESSURES:** 0.50 – 10.0 Bar

**OPERATING TEMPERATURE:** 5°C – 80°C

**SUPPLY:** Suitable for all plumbing Systems

- Made from brass to preserve water quality
- German Vernet cartridges for smooth operation
- Available in assorted finishes
- Solid brass lever

### OPEN OUTLET FLOW (Bar – l/min)

15 Year Guarantee

Bar	1.0	1.5	2.0	2.5	3.0	3.5	4	5
Spout Flow	17.5	19.3	21.6	22.8	24.5	26	27.4	32

Please Note: Flow rate will be dictated by installation configurations. Please ensure to check the appropriate flow restrictor information if applicable. Please refer to the website for fully warranty details.

### CERTIFICATION:

- WRAS APPROVED:
- UPC
- CE
- WATERPARK

FURTHER DETAILS & DIMENSIONS CAN BE FOUND AT [WWW.LUSSOSTONE.COM](http://WWW.LUSSOSTONE.COM) IN THE FEATURE SECTION AND DOWNLOADS TAB OF EACH PRODUCT PAGE.

TEL: 0203 370 4057

EMAIL: [INFO@LUSSOSTONE.COM](mailto:INFO@LUSSOSTONE.COM)

[WWW.LUSSOSTONE.COM](http://WWW.LUSSOSTONE.COM)

THE INFORMATION ON THIS SPECIFICATION DOCUMENT WAS CORRECT AT THE DATE OF ISSUE. SOME VARIATION MAY OCCUR DUE TO MANUFACTURING TOLERANCES AND SITE-SPECIFIC CONDITIONS.