



<b>CONSTRUCTION:</b>	Lead-Free Brass
<b>MOUNT TYPE:</b>	Deck Mounted
<b>CARTRIDGE:</b>	Ceramic
<b>PIPE CONNECTIONS:</b>	G ½"
<b>WORKING PRESSURE:</b>	0.50 - 10.0 Bar
<b>OPERATING TEMPERATURE:</b>	5°C - 80°C
<b>DIMENSIONS FOR FITTING:</b>	35 - 38mm Diameter Hole
<b>SUPPLY:</b>	Suitable for all plumbing systems

- Made from brass to preserve quality
- Citec cartridges for smooth operation
- Neoperl aerator
- Available in assorted finishes
- Solid brass lever

**OPEN OUTLET FLOW (Bar – l/min)**

**15 Year Guarantee**

Bar	0.5	1.0	1.5	2.0	3.0	4.0	5.0
Spout Flow	5.2	7.1	8.2	8.7	8.5	8.5	8.8

Please Note: Flow rate will be dictated by installation configurations.  
Please ensure to check the appropriate flow restrictor information if applicable.  
Please refer to the website for full warranty details.

**CERTIFICATION:**

- WRAS APPROVED: 1812403
- UPC
- CE
- WATERMARK

FURTHER DETAILS & DIMENSIONS CAN BE FOUND AT [WWW.LUSSOSTONE.COM](http://WWW.LUSSOSTONE.COM) IN THE FEATURES SECTION AND DOWNLOADS TAB OF EACH PRODUCT PAGE.