



CONSTRUCTION:	Lead-Free Brass
MOUNT TYPE:	Deck Mounted
CARTRIDGE:	Ceramic
PIPE CONNECTIONS:	G ½"
WORKING PRESSURE:	0.50 - 10.0 Bar
OPERATING TEMPERATURE:	5°C - 80°C
DIMENSIONS FOR FITTING:	35 - 38mm Diameter Hole
SUPPLY:	Suitable for all plumbing systems

- Made from brass to preserve quality
- Citec cartridges for smooth operation
- Neoperl aerator
- Available in assorted finishes
- Solid brass lever

OPEN OUTLET FLOW (Bar – l/min)

15 Year Guarantee

Bar	0.5	1.0	1.5	2.0	3.0	4.0	5.0
Spout Flow	5.2	7.1	8.2	8.7	8.5	8.5	8.8

Please Note: Flow rate will be dictated by installation configurations.
Please ensure to check the appropriate flow restrictor information if applicable.
Please refer to the website for full warranty details.

CERTIFICATION:

- WRAS APPROVED: 1812403
- UPC
- CE
- WATERMARK

FURTHER DETAILS & DIMENSIONS CAN BE FOUND AT WWW.LUSSOSTONE.COM IN THE FEATURES SECTION AND DOWNLOADS TAB OF EACH PRODUCT PAGE.